

# **T**estpassport**Q&A**



---

**H i g h e r   Q u a l i t y**

**B e t t e r   S e r v i c e !**

We offer free update service for one year  
[Http://www.testpassport.com](http://www.testpassport.com)

**Exam** : **2B0-012**

**Title** : **ES Switching Edition 4.0**

**Version** : **DEMO**

1. How many static routes can the Matrix C1 support?

- A. 250
- B. 500
- C. 1,000
- D. 2,000

Answer: C

2. Which IP Address Class is reserved for Multicast?

- A. Class A
- B. Class B
- C. Class C
- D. Class D
- E. Class E

Answer: D

3. Which IP address will trigger Remote IP Address Discovery?

- A. 10.1.1.1
- B. 172.16.0.1
- C. 255.255.255.255
- D. 0.0.0.0

Answer: D

4. The Data Link layer of the OSI model defines which sub-layers?

- A. LLC
- B. MAC
- C. CSMA
- D. none of the above
- E. both A & B

Answer: E

5. Which information does a bridge use to build its SAT?

- A. the source's logical address
- B. the source's physical address
- C. the destination's logical address
- D. the destination's physical address

Answer: B

6. What version of management does the Matrix-E1 support?

- A. SNMP-v4
- B. IGMP
- C. SNMP-v3
- D. Level 2

Answer: C

7. Which groups of RMON does the Matrix C2 support?

- A. the C2 supports 4 groups of RMON (groups 1,2,3 and 9)
- B. the C2 supports 4 groups of RMON (groups 1,2,3 and 4)
- C. the C2 supports 5 groups of RMON (groups 1,2,3, 4 and 9)
- D. the C2 supports all 9 groups of RMON

Answer:A

8. What is the first factor considered in the election of a Designated Bridge by 802.1D compliant bridges using the Spanning Tree Algorithm?

- A. the port ID number
- B. the path cost to Root
- C. the bridge MAC address
- D. the bridge priority number

Answer: B

9. What is the default VLAN assignment method for Enterasys 802.1Q switches?

- A. MAC
- B. Port
- C. Protocol type
- D. DSAP or SSAP values

Answer: B

10. What is the command to disable Spanning Tree on Fast Ethernet port #11 in a platinum DFE module in slot #1?

- A. Matrix (rw)-> set spantree portstatus fe.1.11 disable
- B. Matrix (rw)-> set spantree systemadmin fe.1.11 disable
- C. Matrix (rw)-> set spantree systemstatus fe.1.11 disable
- D. Matrix (rw)-> set spantree portadmin fe.1.11 disable

Answer: D

This document was created with Win2PDF available at <http://www.win2pdf.com>.  
The unregistered version of Win2PDF is for evaluation or non-commercial use only.  
This page will not be added after purchasing Win2PDF.