

Testpassport**Q&A**



H i g h e r Q u a l i t y

B e t t e r S e r v i c e !

We offer free update service for one year
[Http://www.testpassport.com](http://www.testpassport.com)

Exam : **922-097**

Title : Comm.Server 1000
Upgrades to RIs.5.0 for
Technicians

Version : DEMO

1. A customer is upgrading an existing Communication Server (CS) 1000S at RIs. 4.5 to a CS 1000E RIs. 5.0 Standard Availability. A CP-PM Call Server card is being installed during the upgrade. The CP-PM Call Server card has been installed into Slot 1 and configured. What is the next sequential step in the upgrade process?

- A. Reboot the card to begin the software installation.
- B. Connect the administration console to Port 0 of the NTAK19EC SDI cable.
- C. Insert the RMD containing the RIs. 4.5 customer database into the faceplate of the CP-PM Call Server card.
- D. Insert the bootable RMD containing software installation files into the faceplate of the CP-PM Call Server card.

Answer: B

2. A customer is upgrading an existing Communication Server (CS) 1000S at RIs. 4.5 to a CS 1000E RIs. 5.0 with a single IP Media Gateway 1000E chassis. In this configuration, which slot in the IP Media Gateway houses the Media Gateway Controller Card?

- A. Slot 0
- B. Slot 1
- C. Slot 2
- D. Slot 3

Answer: A

3. A customer with a Communication Server (CS) 1000E at RIs. 4.5 with an Media Gateway (MG) 1000T containing three chassis is planning to migrate the functionality of the MG 1000T into the CS 1000E High Availability system, and then upgrade the system to RIs. 5.0. The system Signaling Servers are Nortel ISP 1100 servers. What must be done to the Signaling Server to complete the upgrade?

- A. Upgrade the server software to RIs. 5.0 only.
- B. Replace the hardware to CP-PM Signaling Server.
- C. No action is required; the Signaling Server can remain at RIs. 4.5.
- D. Upgrade the memory to 1 GB followed by a software upgrade to RIs. 5.0.

Answer: D

4. A customer is upgrading an existing Communication Server (CS) 1000S at RIs. 4.5 to a CS 1000E RIs. 5.0 Standard Availability with a single IP Media Gateway (MG) 1000E chassis. Which components must be replaced in the MG 1000S to complete the upgrade?

- A. SSC Card
- B. Call Server
- C. Voice Gateway Media Card
- D. Nortel IPS 1100 Signaling Server

Answer: A

5. A customer is upgrading an existing Communication Server (CS) 1000S at RIs. 4.5 to a CS 1000E RIs. 5.0. A CP-PM Call Server card is being installed during the upgrade. Which statements correctly describe the software installation process? (Choose two.)

- A. RIs. 5.0 software does not need to be installed on the CP-PM Call Server.
- B. The Software Install tool is launched on the first boot of the CP-PM Call Server.
- C. RIs. 5.0 software must be loaded onto the CP-PM Call Server using a bootable RMD.
- D. A bootable RMD must be created containing the RIs. 5.0 software and operating system.

Answer: CD